NEW VARIFEED™ GRAIN HEADERS

760CG

New 760CG VariFeed™ grain headers allow you to harvest at high field speeds to make full use of the high capacity of New Holland combines. Both the 30- and 35-foot models are compatible with all New Holland CX and CR combines.

EFFORTLESS, ON-THE-GO KNIFE ADJUSTMENT

The floor of Varifeed™ heads travels 23 inches, and allows you to adjust knife position fore and aft right from the cab. This electro-hydraulic knife advancement and retraction allows you to make changes depending on crop height and density to assure proper crop flow. The header floor remains closed in all knife positions, without the need for filler plates or drive belt changes.

If you direct-cut canola, Varifeed heads are ideal. The 23 inches of floor travel allow ample room for the bushy canola crop. Vertical knives are available to slice through tangled crop.

SMOOTH CROP FLOW FROM THE START

The Varifeed head design encourages operators to regulate the flow of crops so there's an even crop layer from start to finish, maximizing the efficiency of your New Holland combine. With the varying distance between knife and intake auger, the header reel plays a more important role in crop guidance and crop feeding. It is hydraulically driven for increased flexibility and to provide ample torque in heavy crops.

BUILT-IN DURABILITY

Rugged frame construction and heavy-duty features like the high-speed knife drive, large-diameter auger and the extended reach of the reel tines helps assure reliability and impressive cutting and feeding capacity.

Varifeed™ Grain Header Compatibility	30-foot	35-foot
Super Conventional Combines	CX8070	CX8070
	CX8080	CX8080
	CX8090	CX8090
Twin Rotor® Combines	CR6090	CR6090
	CR7090	CR7090
	CR8080	CR8080
	CR8090	CR8090
	CR9090	CR9090

NEW HOLLAND VARIFEED™ GRAIN HEADERS

Cutting Width	30' & 35'	**Auger Diameter**	26" (660mm)
Knife Drive	Single	**Auger Finger Pattern**	Straight
Knife Speed	650 cycles per minute	**Auger Drive Chain**	RC60 HD
PTO Driveline protection	Yes	**Reel Drive**	Hydraulic w/chain reduction
PTO storage position hook	Yes	**Extended Lift Reel Hydraulic Cylinders**	Yes
Lateral Tilt Ready Driveline	Yes	**Hydraulic reel fore/aft control**	Yes
Single lever, quick attach header latching	Yes	**Sliding reel cam adjustment**	Yes
Single point/single lever hydraulic coupler	Yes	**Reel speed sensor**	Yes
Single point electrical wiring coupler	Yes	**Automatic Header Height Control with Terrain Tracer**	Yes, 3 sensor system
Cutterbar position sensor	Yes		

NEW HOLLAND TOP SERVICE℠

TOTAL SUPPORT, TIMELY INFORMATION FOR NEW HOLLAND CUSTOMERS.

NEW HOLLAND TOP SERVICE℠ 866-NEW-HLND 866-639-4563

TOP AVAILABILITY
Year-round support and information — just by calling one toll-free number.

TOP SPEED
Express parts delivery when and where you need it.

TOP PRIORITY
Fast-track solutions maximize your productivity — because your harvest can't wait.

TOP SATISFACTION
We drive and track the solution you need, keeping you informed — until you are back to work.

TOP SERVICE IS MANAGED IN CLOSE PARTNERSHIP WITH NEW HOLLAND DEALERS AND SERVICE TEAMS.

YOUR NEW HOLLAND DEALER

NEW HOLLAND AGRICULTURE
FARM RAISED™

Learn more at **www.newholland.com/na**

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.

© 2011 CNH America LLC. All rights reserved. New Holland and CNH Capital are registered trademarks of CNH America LLC. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH America LLC, are the property of those respective companies.

THINK SAFETY

Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.

NHXXXXXXXX • 0611XX • XX • PRINTED IN U.S.A.