

NEW VARIFEED™ GRAIN HEADERS

760CG



New 760CG VariFeed™ grain headers allow you to harvest at high field speeds to make full use of the high capacity of New Holland combines. Both the 30- and 35-foot models are compatible with all New Holland CX and CR combines.

EFFORTLESS, ON-THE-GO KNIFE ADJUSTMENT

The floor of VariFeed™ heads travels 23 inches, and allows you to adjust knife position fore and aft right from the cab. This electro-hydraulic knife advancement and retraction allows you to make changes depending on crop height and density to assure proper crop flow. The header floor remains closed in all knife positions, without the need for filler plates or drive belt changes.

If you direct-cut canola, VariFeed heads are ideal. The 23 inches of floor travel allow ample room for the bushy canola crop. Vertical knives are available to slice through tangled crop.

SMOOTH CROP FLOW FROM THE START

The VariFeed head design encourages operators to regulate the flow of crops so there's an even crop layer from start to finish, maximizing the efficiency of your New Holland combine. With the varying distance between knife and intake auger, the header reel plays a more important role in crop guidance and crop feeding. It is hydraulically driven for increased flexibility and to provide ample torque in heavy crops.

BUILT-IN DURABILITY

Rugged frame construction and heavy-duty features like the high-speed knife drive, large-diameter auger and the extended reach of the reel tines helps assure reliability and impressive cutting and feeding capacity.

Varifeed™ Grain Header Compatibility

Super Conventional Combines

30-foot

CX8070
CX8080
CX8090

35-foot

CX8070
CX8080
CX8090

Twin Rotor® Combines

CR6090
CR7090
CR8080
CR8090
CR9090

CR6090
CR7090
CR8080
CR8090
CR9090

NEW HOLLAND VARIFEED™ GRAIN HEADERS

Cutting Width	30' & 35'	Auger Diameter	26" (660mm)
Knife Drive	Single	Auger Finger Pattern	Straight
Knife Speed	650 cycles per minute	Auger Drive Chain	RC60 HD
PTO Driveline protection	Yes	Reel Drive	Hydraulic w/chain reduction
PTO storage position hook	Yes	Extended Lift Reel Hydraulic Cylinders	Yes
Lateral Tilt Ready Driveline	Yes	Hydraulic reel fore/aft control	Yes
Single lever, quick attach header latching	Yes	Sliding reel cam adjustment	Yes
Single point/single lever hydraulic coupler	Yes	Reel speed sensor	Yes
Single point electrical wiring coupler	Yes	Automatic Header Height Control with Terrain Tracer	Yes, 3 sensor system
Cutterbar position sensor	Yes		

NEW HOLLAND TOP SERVICESM

TOTAL SUPPORT, TIMELY INFORMATION FOR NEW HOLLAND CUSTOMERS.



TOP AVAILABILITY

Year-round support and information — just by calling one toll-free number.

TOP SPEED

Express parts delivery when and where you need it.

TOP PRIORITY

Fast-track solutions maximize your productivity — because your harvest can't wait.

TOP SATISFACTION

We drive and track the solution you need, keeping you informed — until you are back to work.

TOP SERVICE IS MANAGED IN CLOSE PARTNERSHIP WITH NEW HOLLAND DEALERS AND SERVICE TEAMS.

YOUR NEW HOLLAND DEALER



Learn more at www.newholland.com/na

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.

© 2011 CNH America LLC. All rights reserved. New Holland and CNH Capital are registered trademarks of CNH America LLC. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH America LLC, are the property of those respective companies.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.

NHXXXXXXX • 0611XX • XX • PRINTED IN U.S.A.