

NEW! New Holland Guardian™ Front Boom Sprayers

SP.240F SP.240F XP SP.275F SP.365F



Step into the productivity of a new Guardian front boom sprayer from New Holland and you quickly protect your acres with less fatigue, less downtime. In addition to the many advantages of having the boom in front, these new sprayers also offer the highest horsepower, the largest tank size, the smoothest suspension, the highest ground clearance and the tightest turning radius.

Never look back

With the boom in front, you get the best of all views and never need to turn in your seat to monitor spraying action. Nozzles are located behind the boom, so you have a complete, unrestricted view of every nozzle. Since you have such good visibility, you can run the boom closer to the ground to control drift. Spray is delivered into the crop before the first tires go over it, eliminating the potential for dust to neutralize the spray.

More acres per hour

Select from four models up to 365 horsepower with a choice of tank sizes up to an industry-leading 1,600

gallons and boom widths up to 120 feet so you can cover acres fast. A nearly-perfect 50/50 weight distribution allows for maximum traction and minimum compaction. And, the six-foot ground clearance means you can get into the field for spraying just about any time during the growing season.

Comfortable, acre after acre

The roomy, quiet Guardian™ cab is designed for comfort and easy control so your operators experience less fatigue and increased productivity for long hours on the job.

- The unique four-wheel independent suspension provides the smoothest ride in the industry
- High-back air-ride seat and tilting telescoping steering wheel add comfort for every operator
- 14 adjustable halogen lights are standard for low-light conditions and extended night operation
- Industry-leading 15-foot turning radius provides ultimate maneuverability
- Engine is mounted in the rear for a quieter cab

Guardian™ Front Boom Sprayer Specifications



MODEL	SP.240F	SP.275F	SP.365F
Horsepower, (kW)	240 (179) standard 275 (205) XP optional	275 (205)	365 (272)
Drive description	4-wheel hydrostatic drive		
Product tank size, gallons (l)	1000 or 1200 (3785 or 4542)	1200, 1400 or 1600 (4542, 5300 or 6057)	
Product tank material	Poly or Stainless steel	Stainless steel	
Boom size, ft. (m)	90 or 100 (27 or 30)	90, 100 or 120 (27, 30 or 37)	



The comfortable Guardian™ cab gives you a clear view of the tires, the crop, and each nozzle tip along the entire width of the boom.



A large platform provides easy access to the cab, tanks and rear engine compartment for convenient servicing.

The convenient armrest console includes monitors at the front for on-the-go information and the multi-function joystick that provides complete hydrostatic control and fingertip controls for boom height, wing tilt, master shutoff and individual section shutoff switches.



Visit our Web site at www.newholland.com/na Or, call toll-free: 1-888-290-7377

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.